

SAFETY DATA SHEET (SDS) EASI-PLANK SPC HYBRID FLOORING

1 COMPANY DETAILS

Company: Homemirus Pty Ltd trading as Preference Floors Pty Ltd
Address: Unit A / 31 Sturt Street Smithfield New South Wales 2164
Telephone: 02 97381188
Facsimile: 02 97381199
Emergency: 02 97381188 Normal office hours only.

2 PRODUCT IDENTIFICATION

Product Name: EASI-PLANK SPC HYBRID
Product Code: VE
Product Use: Floor covering
UN Number: N/A
Packaging Group: N/A
Hazchem Code: N/A

2.1 Ingredients

Principle constituents, Poly Vinyl Chloride, DOTP, Calcium Carbonate, Acrylate, Calcium-zinc stabiliser, UV Cured Acrylic & EVA Foam.

2.2 Physical Data

Appearance: Solid SPC Hybrid Plank
Odour: ND
Boiling Point: N/A
Vapour Pressure: Coating only @ 25°C

Vapour Density: Coating only @ 25°C, .95-2.05 /cmm3
Solubility in Water: N/A
Specific Gravity: N/A
Flash Point: Coating > 70°C. Flammability Index: Critical Radiant Flux, 10.9kW/m2
Volatile Organics (VOC): <0.5
Formaldehyde: E1 Floor Score Indoor Air Quality Certified to SCS –EC10.3-2014 v4.0
Respirable Silica Dust: Zero Content

3 HEALTH HAZARD DATA

Dust mask or dust extraction should be used to minimise any inhalation of dust particulates.

3.1 Health Effects

Skin: Wash with tepid soapy water.
Eyes: Flush with cool water for at least 10 minutes and seek medical attention.
Swallowed: Wash mouth and lips with water and seek urgent medical attention.
Inhaled: Move to fresh air, wash with water and seek medical attention if effects persist.

3.2 First Aid

Skin: Wash with tepid soapy water.
Eyes: Flush with cool water for at least 10 minutes and seek medical attention.
Swallowed: Wash mouth and lips with water and seek urgent medical attention.
Inhaled: Move to fresh air, wash with water and seek medical attention if effects persist.
First Aid Facilities: Eye wash facilities, soap and water.

4 PRECAUTIONS OF USE

Heavy packs. Safe lifting procedures should be followed.

4.1 Exposure Standards

Exposure Guidelines: None established by OHS
Engineering Controls: N/A

4.2 Personal Protection

Respiratory Protection: Use a certified dust mask when cutting to minimise dust inhalation
Skin Protection: N/A
Eye Protection: Use safety goggles when cutting to minimise dust, splintering & chipping
Hygiene: N/A

4.3 Flammability

Fire Hazards: Combustible Solid, Core stable up to 200°C

5 SAFE HANDLING INFORMATION

Safe lifting methods should be used.

5.1 Handling and Storage

Storage: Dry temperature conditions
Transport: Not classified as a Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by road or rail

5.2 Environmental and Disposal

Spills and leaks: N/A
Disposal Method: Recycle

5.3 Fire and Explosion Data

Fire & Explosion: Combustible solid
Extinguishing Media: Water fog, carbon dioxide, foam, dry chemical, sand
Fire Fighting Equipment: Under fire conditions, product generates irritating and hazardous vapors and toxic fumes. Fire fighters should wear self-contained breathing apparatus in addition to the protective clothing should be worn. Hazardous decomposition; smoke, hydrogen sulphide, carbon monoxide and carbon dioxide.

6 CONTACT POINT

Telephone: 02 97381188
Address: Unit A/31 Sturt Street Smithfield New South Wales 2164

Disclaimer: Preference Floors has used its reasonable endeavors to ensure the accuracy and reliability of the information contained herein and, to the extent permitted by law, will not be liable for any inaccuracies, omissions or errors in this information nor for any actions taken in reliance on this information. Products must be installed in accordance with relevant installation recommendations and industry best practices.

© Homemirus Pty Ltd trading as Preference Floors Pty Ltd.