

- Coated with a 10% UV cured acrylic matte and brushed faced for added texture
- The 3mm nominal hardwood top layer allows re-sanding and re-coating for a long service life
- · Each board is end matched and tongue and grooved for a tight board fit and consistent finish
- The clear coating highlights the natural colour and timber finishes
- No mess and fumes from sanding and finishing
- PEFC certified
- Now available in popular metallon XL<sup>™</sup> colours Aztec White and Sterling.

## **Installation Requirements**

Pentarch Forestry<sup>™</sup> Engineered Herringbone Parquetry<sup>™</sup> must be glued down over a level subfloor such as a concrete slab, particleboard or plywood sheeting or over old timber floors. For further information, see the Pentarch Forestry<sup>™</sup> Engineered Herringbone Parquetry<sup>™</sup> installation guide. It is recommended that parquetry flooring is installed by a professional as it requires specific methodology and equipment.

# **Specifications**

Natural Herringbone Parquetry

Product	6+Pallets	2+Pallets	Job Lot
134 x 670 x 14mm	\$97.64m²	\$101.21m <sup>2</sup>	\$105.97m <sup>2</sup>
122 x 610 x 14mm	\$76.62m <sup>2</sup>	\$79.43m <sup>2</sup>	\$83.16m <sup>2</sup>

# **Species**

## **Blackbutt**

## **Spotted Gum**



## metallon XL™ Parquetry

Product	6+Pallets	2+Pallets	Job Lot
122 x 610 x 14mm	\$84.30m <sup>2</sup>	\$87.37m <sup>2</sup>	\$91.50m <sup>2</sup>

### **Aztec White**



## **Sterling**



Note: Variations within a timber species are normal, therefore photographs, samples and displays can only be indicative of colour and should not be used for final selection. It is normal for natural timber products to react to changes in atmospheric and environmental conditions such as humidity and temperature.

www.pentarch.com.au/timberproducts.html

National free call 1800 818 317



